


Lubricants for **AUTOMOTIVE**

LUBRICANTS IN CONSTANT EVOLUTION



sash@lubricantes-sash.com



www.lubricantes-sash.com



+34 961 464 843

ACEITES LUBRICANTES SASH

SASH
LUBRICANTS®

INDEX



PACKAGING

PACKAGING DRUM

PACKAGING 5L

PACKAGING 20L

PACKAGING 1L

PACKAGING 4L



Lubricants for
LIGHT
vehicles



ESTER RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
RACING ESTER	10W-60	100% Synthetic	SN	-	-

HYBRID RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
HYBRID GF6	0W-16	100% Synthetic	SP (LICENSE 61307) ILSAC GF-6B	-	RENAULT AN2022
	0W-20		SP (LICENSE 61315) ILSAC GF-6A		-
	0W-30		SP ILSAC GF-6A		
	5W-20		SP (LICENSE 61319) ILSAC GF-6A		
	5W-30		SP (LICENSE 61317) ILSAC GF-6A		
	5W-40		SP		
	10W-30		SP (LICENSE 61318) ILSAC GF-6A		

FLAGSHIP RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
FLAGSHIP GLV	0W-8	100% Synthetic	-	-	JASO GLV-1 · MAZDA · MITSUBISHI NISSAN · TOYOTA
FLAGSHIP 971	0W-20		SN PLUS / SP RC ILSAC GF-6A	C5,C6	MB 229.71 (Approval) · BMW LONGLIFE-17FE+ OV 040 1547 · GM DEXOS D · VCC RBS0-2AE JLR 03.5006 / 03.5006 · FIAT 9.55535-GSX CHRYSLER MS 12145 · RN 0700 / 0710
FLAGSHIP EVOLUTION			-	C5	VW 508.00 / 509.00 PORSCHE C20 · FORD WSS-M2C956-A1
FLAGSHIP 517			-	C5	RN 17FE



FLAGSHIP RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
FLAGSHIP RBO	0W-20	100% Synthetic	SN Approval 50860	C5	VCC RBS0-2AE (Approval 8751149)
FLAGSHIP C5 2010			SN PLUS	C5	OV 040 1547 · A20 · PSA B71 2010 FIAT 9.55535-DM1
FLAGSHIP 952			SN PLUS/SP ILSAC GF-5	C5,C6	MB 229.71 · OV 040 1547 · GM DEXOS D JLR 03.5006 / 51.5122 FORD WSS-M2C952-A1 / WSS-M2C947-A FORD WSS-M2C947-B1 / WSS-M2C962-A1 / WSS-M2C954 A1
FLAGSHIP G15			SQ ILSAC GF-7A	-	GM DEXOS 1 GEN. 3 · GM 6094 M · CHRYSLER MS-6395 FIAT 9.55535-CR1 · FORD WSS-M2C947-A / WSS-MSC947-B1 FORD WSS-M2C962-A1 · TOYOTA · HONDA · NISSAN MAZDA · HYUNDAI
FLAGSHIP C3 504/7	0W-30	100% Synthetic	SN/CF	C2,C3	VW 504.00 / 507.00 · BMW Long Life-04 PORSCHE C30 · MB 229.52 FIAT 955535.GS1 / 955535.DS1
FLAGSHIP C2 950			SN/CF	C2	FORD WSS-M2C-950A · JLR 03.5007 FIAT 9.55535-GS1/DS1 · IVECO 18-1811 SC1 LV
FLAGSHIP C2 2312			-	C2	PSA B71 2312 · FORD WSS-M2C-934B · JLR 03.5007 HONDA · MITSUBISHI · SUZUKI · TOYOTA
FLAGSHIP 19FE			SP	C2,C3	BMW LL-04, BMW LL-12 FE, BMW LL-19 FE · KIA ENGINE OIL MB 229.61 · FORD WSS-M2C950-A · OPEL OV0401547 PSA B71 2290 / B71 2312 · STELLANTIS FPW9.55535-DH1
FLAGSHIP VCC377			SL	A5/B5 A7/B7	VCC 95200377
FLAGSHIP 948B	5W-20	100% Synthetic	SN	-	FORD WSS-M2C 948B · JLR 03.5004
FLAGSHIP C1	5W-30	100% Synthetic	-	C1	JASO DL-1 · FORD WSS-M2C 934B · JLR 03.5005 MAZDA (DPF & FAP)
FLAGSHIP C2 PSA			SN/CF	C2	PSA B712290 · BMW Long Life-04
FLAGSHIP 517			-	C3	RN17
FLAGSHIP C2/C3 547			SN/CF	C2,C3	VW 504.00/507.00 · BMW Long Life-04 · MB 229.52 PORSCHE C30 · PSA B712290 · GM OPEL DEXOS 2 FIAT 9.55535-DS1 / 9.55535-GS1
FLAGSHIP EVOLUTION			SN/CF	C3	VW 504.00 / 507.00 · BMW Long Life-04 PORSCHE C30 · MB 229.51
FLAGSHIP C3 504/7			SN/CF	C3	VW 504.00 / 507.00 · BMW Long Life-04 PORSCHE C30 · MB 229.52
FLAGSHIP C23			SN PLUS/CF	C2,C3	PSA B71 2290 / B71 2297 · GM DEXOS 2 FIAT 9.55535-S1 / 9.55535-S2 · VW 502.00 / 505.01 RN 0700 · MB 229.52 · STELLANTIS FPW9.55535/03
FLAGSHIP C3 DEXOS			SN/CF	C3	GM OPEL DEXOS 2 · MB 229.52 · PSA B712297 VW 502.00 / 505.00 / 505.01
FLAGSHIP C4			-	C4,C3	MB 226.51 · RN 0720
FLAGSHIP F 913D			SN	A5/B5 A7/B7	FORD WSS-M2C 913D · JLR 03.5003
FLAGSHIP G15			SP/SN PLUS ILSAC GF-6A	-	GM DEXOS 1 GEN. 3 · GM 6094 M · CHRYSLER MS-6395 FIAT 9.55535-CR1 · FORD WSS-M2C929-A / WSS-MSC946-A FORD WSS-M2C961-A / WSS-M2C946-B1 · TOYOTA · HONDA NISSAN · MAZDA · HYUNDAI
FLAGSHIP DRACO	0W-40	100% Synthetic	SN/CF	A3/B4	PORSCHE A40 · MB 229.5 · VW 502.00 / 505.00 BMW Long Life-01 · RN 0700 / 0710 FORD WSS-M2C937-A
	5W-30				MB 229.5
	5W-40				MB 228.3 / 229.1
	10W-60				
FLAGSHIP C3	5W-40	100% Synthetic	SN/CF	C3	MB 229.52 · PORSCHE A40 · GM DEXOS 2 RN 0700 / 0710 · FORD WWS-M2C 917A BMW Long Life-04 · VW 502.00 / 505.00 / 505.01



STATUS CAR RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
STATUS CAR	5W-30	Synthetic	SN/CF	A3/B4	GM-LL B-025 · VW 502.00 / 505.00 · BMW LL-01 RN 0700 / 0710 · MB 229.5 FIAT 9.55535-G1 · PSA B712296
STATUS CAR	5W-40				GM-LL B-025 · MB 229.5 · VW 502.00 / 505.00 BMW LL-01 · RN0700 / 0710 · PORSCHE A40 FIAT 9.55535-M2 · PSA B712296
STATUS GLK	10W-40				MB 229.1 / 229.3
STATUS GLOBAL	10W-40	Semi-Synthetic	SN/CF		GM-LL B-025 · RN 0700 / 0710 VW 502.00 / 505.00 · MB 229.1 FIAT 9.55535-G2
STATUS XP	10W-40		SL/CF-4		VW 501.01 / 505.00
STATUS GLK	15W-50		SN/CF		MB 229.1 / 229.3

RODER RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
RODER XP	15W-40	Mineral	SL/CF-4	A3/B3	VW 501.01 / 505.00 MB 229.1
RODER PLUS	20W-50				
RODER S.S III	10W		CF/SF	-	ALLISON C3 · CAT TO-2 MAN 270 · MB 228.0 · MTU Type I
	30				
	40				
	50				

GAS RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
GAS	5W-30	Synthetic	SN	-	-
	5W-40			C3	
	20W-50			-	



Lubricants for
HEAVY
vehicles



SASH
LUBRICANTS®

GAMA GALACTIC

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
GALACTIC U1804	0W-20	100% Synthetic	-	-	IVECO 18-1804 TLV LSCTR I139.D14
GALACTIC E3977	5W-20	Synthetic	-	-	MAN M3977 SCANIA LDF-5
GALACTIC FA-4	5W-30	Synthetic	FA-4/SN	-	DTFR 15C130 (MB 228.61) · CUMMINS CES 20087 DETROIT DIESEL 93K223 · MACK EOS-5 · RENAULT RLD-5 VOLVO VDS-5 · FORD WSS-M2C214-B1
	10W-30				JASO DH-2 · CUMMINS CES 20087 DTFR 15C130 (MB 228.61) · DETROIT DIESEL 93K223 RENAULT RLD-5 · VOLVO VDS-5 · MACK EOS-5
GALACTIC CK-4	5W-40	Semi-Synthetic	CK-4, CJ-4/SM	E7,E11	DTFR 15C100 (MB 228.31) · MAN M 3275/M375 VOLVO VDS-4 / VDS 4.5 · RENAULT RLD-3/RLD-2/VI RLD-4 CATERPILLAR ECF-3/ECF-2/ECF-1-A · JASO DH-2 CES 20076/20077/20078/20081/20086 · DEUTZ DQC III-10-LA GLOBAL DHD-1 · MTU type 2.1/type 2/type 1 DETROIT DIESEL DDC 93K218, 93K215, 93K222 MACK EO-O PP / EO-N Premium Plus / EOS-4.5
	10W-30		CK-4/CJ-4/CI-4+/- CI-4/CH-4/SN		JASO DH-2 · CATERPILLAR ECF-3/ECF-2/ECF-1a DEUTZ DQC III-18 LA · MTU Category 2.1 DTFR 15C100 (MB 228.31) · VOLVO VDS-4.5 · MACK EOS-4.5 RENAULT VI RLD-3 · CUMMINS CES 20086 · DAF PSQL 2.4 DETROIT DIESEL DFS 93K222 · MAN M3775 · ISUZU KOMATSU · HITACHI · JCB · KOBELCO · CASE
	10W-40		SN/CK-4 Homologación 62521		MB 228.31 (Homologación) · DTFR 15C100 (MB 228.31) VOLVO VDS-4.5 · DEUTZ DQC III-10 LA · MTU Type 2.1 MACK EO – S-4.5 · CUMMINS CES 20086 · CAT ECF-3 RENAULT RVI RLD-4/RLD-3 · MAN M3775 DETROIT DIESEL DFS 93K222 IVECO 18-1804 TLS CK4 C.T.R. 037.F21 · 18-1804 TLS E9
	15W-40		SN/CK-4 Homologación 62526		MB 228.31 (Homologación) · DTFR 15C100 (MB 228.31) VOLVO VDS-4.5 · DEUTZ DQC III-10 LA · MTU Type 2.1 MACK EO – S-4.5 · CUMMINS CES 20086 · CAT ECF-3 RENAULT RVI RLD-4/RLD-3 · MAN M3775 DETROIT DIESEL DFS 93K222 FORD 171-F1
GALACTIC E900	10W-30	Synthetic	CJ-4/SN	E7,E11	VOLVO VDS-4/VDS-3 MACK EO – M+ MAN M 3575/3275 RENAULT RVI RLD-3 MTU Type 2.1 DTFR 15C100 (MB 228.31) DTFR 15B110 (MB 228.3) CUMMINS CES 20081 SCANIA Low Ash CAT ECF 1A,2A,3
	10W-40				
	15W-40				
	15W-50				
GALACTIC E600	5W-30	100% Synthetic	CK4	E7,E8,E11	MAN M3271-1/M3477/M3677/M3775 CATERPILLAR ECF-3 · MACK EOS-4.5 · VOLVO VDS-4.5 DTFR 15C100 (MB 228.31) · DTFR 15C110 (MB 228.51) DTFR 15C120 (MB 228.52) · MTU type 3.1/2.1 RVI RLD-4 / RLD-3 · DETROIT DIESEL 93K222 JASO DH-2-17 · DEUTZ DQC IV-18LA · SCANIA LDF-4 CUMMINS CES20086/CES20081
	10W-40				MAN M3271-1/M3477/M3677/M3775 CATERPILLAR ECF-3 · MACK EOS-4.5 · VOLVO VDS-4.5 DTFR 15C100 (MB 228.31) · DTFR 15C110 (MB 228.51) DTFR 15C120 (MB 228.52) · MTU type 3.1/2.1 RVI RLD-4 / RLD-3 · DETROIT DIESEL 93K222 JASO DH-2-17 · DEUTZ DQC IV-18LA · SCANIA LDF-4 CUMMINS CES20086/CES20081 DAF PSQL 2.4 LD
	10W-30				
GALACTIC E400	5W-30	100% Synthetic	CI-4	E4,E7	MAN M3277 · DTFR 15B120 (MB 228.5) VOLVO VDS-3 · SCANIA LDF-3 RENAULT RXD IVECO DAF E4 MACK EO-M+ IVECO 18-1804 TFE E4 CTR I023.M01
	10W-40				
GALACTIC E700	10W-40	Synthetic	SL/CI-4	A3/B4 & E7	GLOBAL DHD-1 · MAN M3275 · IVECO-PEGASO DAF XF · MACK TRUCK EO-M+ · MB 229.1 DTFR 15B110 (MB 228.3) · RENAULT RLD-2 · SCANIA LDF HINO-ISUZU DH-1 · VOLVO VDS-3
GALACTIC MULTI	5W-30	100% Synthetic	CJ-4	E4,E7,E8,E11	VOLVO VDS-4 · MTU Oil Category 2.1/3.1 DTFR 15C100 (MB 228.31) · DTFR 15C110 (MB 228.51) DTFR 15C120 (MB 228.52) · DEUTZ DQC IV-18LA MAN M3275 / 3277 / 3575 / 3677 / 3477 MACK EO-O PREMIUM PLUS · CUMMINS CES20081 CATERPILLAR ECF-3 · DDC PGOS 93K218 · RVI RLD-2/RLD-3 JASO DH-2 · IVECO 18-1804 TLS E6 CTR I720.I12
	10W-30				VOLVO VDS-4 · MTU Oil Category 2.1/3.1 DTFR 15C100 (MB 228.31) · DTFR 15C110 (MB 228.51) DTFR 15C120 (MB 228.52) · DEUTZ DQC IV-18LA MAN M3275 / 3277 / 3575 / 3677 / 3477 MACK EO-O PREMIUM PLUS · CUMMINS CES20081 CATERPILLAR ECF-3 · DDC PGOS 93K218 RVI RLD-2/RLD-3 · JASO DH-2
	10W-40				VOLVO VDS-4 · MTU Oil Category 2.1/3.1 DTFR 15C100 (MB 228.31) · DTFR 15C110 (MB 228.51) DTFR 15C120 (MB 228.52) · DEUTZ DQC IV-18LA MAN M3275 / 3277 / 3575 / 3677 / 3477 MACK EO-O PREMIUM PLUS · CUMMINS CES20081 CATERPILLAR ECF-3 · DDC PGOS 93K218 · RVI RLD-2/RLD-3 JASO DH-2 · IVECO 18-1804 NG2 / IVECO 18-1809 NG2



MASTER RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MASTER CK	15W-40	Semi-Synthetic	CK-4	E7,E9	DTFR 15C100 (MB 228.31) · DTFR 15B110 (MB 228.3) MAN M-3575, MAN M3271-1 CAT ECF-3 · MTU 3.1 FORD WSS-M2C171-F1 CUMMINS CES 20086 · CES 20081 VOLVO VDS-4.5 · MACK EOS-4.5 DEUTZ DQC IV-10 LA · RENAULT RLD-4 IVECO TLS E9
	15W-50				
MASTER ULTRA THPD E7	15W-40	Mineral	CI-4/SN	A3/B4 & E7	MAN M3275 IVECO-PEGASO DAF XF · MB 229.1 RENAULT RLD-2 DTFR 15B110 (MB 228.3) SCANIA LDF VOLVO VDS-3 DEUTZ DQC III-10
	15W-50				
	20W-50				
	25W-60		CH-4/CF	E7	MAN M3275-1 · RENAULT RD-2 · MACK EO-L PLUS DTFR 15B110 (MB 228.3) · VOLVO VDS-2 CAT ECF-1A · CUMMINS CES 20077 MTU TYPE 2 · DEUTZ DQC II-05

MASTERGAS RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MASTERGAS	15W-40	Mineral	-	-	Detroit 93K216 CUMMINS CES 20085

CAPRIN SUPERIOR RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
UPPER CAPRIN PLUS	40	Mineral	CF-2	-	GM EMD engines · General Electric · Gen 4 LMOA - generation V Alco, Baldwin and Fairbanks-Morse engines



OFF ROAD RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
SASH DEO	10W-30	Mineral	CI-4/SN	E7	CAT ECF-2 CUMMINS CES 20078 VOLVO VDS-3 · JASO DH-1 MACK EO-N · MACK EO-M PLUS RENAULT RLD-2 MTU CATEGORY 2 DTFR 15B110 (MB 228.3) IVECO 18-1804 T2 E7 CTR I517.F06
	15W-40				
SASH FDO	50	Mineral	-	-	CAT FD-1
	60				
SASH FDO SYN	-	Semi-Synthetic			
SASH TDTO	10W	Mineral	CF, MT-1	-	ALLISON C-4 · CATERPILLAR TO-4 · ZF TE-ML 03C DANA Powershift Transmissions KOMATSU KES07.861.1 · VICKERS (35VQ25)
	30				ALLISON C-4 · CATERPILLAR TO-4 DANA Powershift Transmissions KOMATSU KES07.861.1 · ZF TE-ML 03C & ZF TE-ML 07F
	50				ALLISON C-4 · CATERPILLAR TO-4 KOMATSU KES07.861.1 TREMATIC/TTC
SASH SMT	-	Mineral	-	-	CAT TO-4M, TO-4 · ALLISON C-4

GAS ENGINE RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
ABRAXAN 1000	15W-40	Mineral	CF	-	GE Jenbacher for TA 1000-1109 (class B fuel gas, Series 2 & 3)
	40				
ABRAXAN 5000	10W-30	Mineral	-	-	Waukesha CUMMINS L10 – M11 MAN Co-gen MWM DEUTZ Dresser-Rand Category II, III CAT 3300, 3400, 3500, 3600 Series Wartsila SACM 150/175 SG SIn
	15W-40				
	20W-50				
	40				
ABRAXAN 6000	15W-40	Mineral	-	-	CUMMINS CES 20074 CUMMINS B5.9G, C8.3G DDC Series 50G and 60G
	40				
ABRAXAN 8000	15W-40	Mineral	-	-	Waukesha CUMMINS L10 – M11 MAN Co-gen MWM DEUTZ Dresser-Rand Category II, III CAT 3300, 3400, 3500, 3600 Series Wartsila SACM 150/175 SG SIn
	40				



A close-up photograph of a motorcycle's rear wheel and tire. The tire is black with a prominent tread pattern. The wheel is silver with multiple spokes. A silver disc brake is visible behind the tire. The motorcycle is parked on a gravel surface. The image is partially covered by a dark blue diagonal banner on the left side, which contains the text 'Lubricants for MOTORCYCLES'. An orange diagonal line runs across the image from the top right towards the bottom left.

Lubricants for **MOTORCYCLES**

MOTOLUB STER 4T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOLUB STER 4T	10W-40	100% Synthetic	SN	-	JASO MA2 (T903:2016) Con tecnología de Éster. Aceite de competición de alto rendimiento.
	10W-60				

NEW

MOTOLUB MAXIMA 4T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOLUB MAXIMA ELITE 4T	5W-40	100% Synthetic	SN	-	JASO MA2 (T903:2016) Approval M034LEC004
	10W-50				JASO MA2 (T903:2016) Approval M034LEC003

MOTOLUB PLUS 4T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOLUB PLUS 4T	10W-40	Synthetic	SN Approval 64158	-	JASO MA2 (T903:2016) Approval M034LEC005
	15W-50		SN		JASO MA2 (T903:2016)
	20W-50		SN Approval 50824		JASO MA2 (T903:2016) Approval M034LEC001

MOTOLUB BIKER 4T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOLUB BIKER 4T	20W-50	Mineral	SL	-	JASO MA2



MOTOWORLD MAXIMA GAMA 2T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOWORLD MAXIMA 2T	-	100% Synthetic	TC+	-	JASO M345 FD · ISO/L/EGD · TISI APRILIA DFI

MOTOWORLD PLUS 2T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOWORLD PLUS 2T	-	Semi-Synthetic	TC	-	JASO M345 FC · ISO/L/EGD · TISI

MINOIL MOTOWORLD 2T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MOTOWORLD MINOIL 2T	-	Mineral	TB	-	JASO FB · ISO-L-EGB



Lubricants for
MARINE
industry



SASH
LUBRICANTS®

MARINE LUBE RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	DESCRIPTIONS
MARINE LUBE VR12	15W-40	Mineral	Oil for marine diesel engines specially designed to lubricate the new Euro 3/4 engines with low emission levels and to use light fuel with up to 1% sulfur content.
MARINE LUBE VR15	15W-40	Mineral	Oils for marine diesel engines specially designed for all types of modern 4-stroke fast-speed engines running on marine distillate fuel.

TRUNKLUBE VM RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	DESCRIPTIONS
TRUNKLUBE VM30	30	Mineral	Oil for marine diesel engines specially designed to lubricate new Euro 3/4 engines with low emission levels and to use light fuel with up to 1% sulfur content.
TRUNKLUBE VM30	40	Mineral	Oil for marine diesel engines specially designed for all types of modern 4-stroke medium-speed gas oil or marine diesel oil (MDO) engines. Moderate stress oil.
TRUNKLUBE VM40	30	Mineral	Trunk piston engine oil specially designed for modern 4-stroke marine diesel engines running on intermediate fuel oil (IFO) or heavy fuel oil (HFO).
TRUNKLUBE VM40	40	Mineral	
TRUNKLUBE VM50	40	Mineral	



CYLUBE VL RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	DESCRIPTIONS
CYLUBE VL5	30	Mineral	Marine system lubricant. Premium crankcase lubricant for low-speed crosshead diesel engines.
CYLUBE VL25	50	Mineral	Cylinder oil for low-speed engines developed for modern engines running on distillate fuels and LNG with a sulfur content of up to 0.1%.
CYLUBE VL40	50	Mineral	Cylinder oil for low-speed engines developed for modern engines running on low-sulfur fuels.
CYLUBE VL70	50	Mineral	Cylinder oil for low-speed engines developed to provide good performance at the higher temperatures and pressures of modern engines.
CYLUBE VL100	50	Mineral	Cylinder oil for low-speed engines that withstands the most stringent and corrosive conditions encountered in service.

NAUTICAL 2T & 4T RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
MARINE OUTBOARD 2T	-	100% Synthetic	TD-TSC 4	-	YAMAHA · NMMA TC-W3
MARINE W2 2T	-	Semi-Synthetic	TC	-	NMMA TC-W2
MARINE WORLD 4T	SAE 150W-40	Synthetic	SL	-	NMMA FC-W · HONDA · MERCURY · YAMAHA EVINRUDE/JOHNSON (BRP) · SUZUKI NISSAN · TOHATSU



Lubricants for
MTF & ATF
transmissions

HYPOX - MTF LSD RANGE

Nombre PRODUCTO	Grado de VISCOSIDAD	NATURALEZA	API/ILSAC	NIVEL DE CALIDAD de Constructores
HYPOX WS LSD	75W-90	Synthetic	GL-4/GL-5/GL-5 Limited Slip	ZF TE-ML 05C / D · VW G50/G51 · MIL-L-2105 D GM 1940058/93165388/88862624/88862625
HYPOX W LSD	80W-90	Mineral	GL-5 Limited Slip	MIL-L-2105 B/C/D · ZF TE-ML 05C/12C/21C
HYPOX LSD	90			MIL-L-2105 B · ZF TE-ML 05C/12C/21C

SYNQUERT - MTF RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	API/ILSAC	QUALITY LEVEL of Manufacturers
SYNQUERT	75W-90	100% Synthetic	GL-4/GL-5	MT-1 · MB 235.8 · MACK GO-J · MIL PRF-2105 E · SCANIA STO 1:0 VOLVO 97312 · DAF · IVECO · RENAULT · MAN 341 Z2, E3 / 342 M3 ZF 02B, 07A, 08, 05B, 12L, 12N, 16F, 17B, 19C e 21B
SYNQUERT	80W-140			MT-1 · MACK GO-J · MIL-PRF-2105 E · SCANIA STO-1:0
SYNQUERT 235.11	75W-90		GL-4	MAN 341 TYPE MB · MB 235.11 · ZF TE-ML 08
SYNQUERT MWS	75W-80			F TE-ML 01L, 02L, 08, 16K · IVECO 18-1807 MGS · MB 235.29 MAN 341 TYPE E3 / MAN 341 TYPE Z4 · VOLVO 97307
SYNQUERT Z5	75W-80			VOLVO 97307 · MAN 341 TYPE VR · MAN 341 TYPE Z5 MB TRUCKS DTFR 13D120 (235.29) · VOITH OIL CLASS C IVECO MGS2 · ZF TE-ML 01E / 02E / 16P



ENDURASYN - MTF RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	API/ILSAC	QUALITY LEVEL of Manufacturers
ENDURASYN	75W-80	Synthetic	GL-4/GL-5	SAE J 2360 · MT-1 · MIL -L- 2105 D
ENDURASYN	75W-90			J 2360 · MT-1 · MACK GO-J · MB 235.8 ZF 02B,05B,07A,12B,16F,17B,19C,21B
ENDURASYN	85W-140	Synthetic		MT-1 · MACK GO-J · MIL-PRF-2105 D SCANIA STO-1:0 · DAF API GL-5
ENDURASYN INTEX	75W-80		GL-4+	PSA B71 2330



ENDURANCE - MTF RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	API/ILSAC	QUALITY LEVEL of Manufacturers
ENDURANCE W	75W-80	Mineral	GL-4/GL-5	SAE J 2360 · MT-1 · MIL -L- 2105 D
ENDURANCE W	80W-90			MT-1 · SCANIA STO 1:0 · MB 235.0 MAN 341 TYPE E2 / MAN 342 TYPE Z2 / MAN 342 TYPE M2 ZF TE-ML 02B, 05A, 07, 08, 12L, 12M, 16B, 17B, 19B, 21A VOLVO 97321 · JOHN DEERE JDM J11E CASE MS 1316 · FORD M2C197-A
ENDURANCE W	85W-140			VOLVO 97310 · ZF TE-ML 05A, 12E, 16D, 21A DAF API GL-5 · MIL-L-2105 D · SCANIA STO 1:0
ENDURANCE	90		GL 5	US MIL-L-2105 D · FORD SQM-2C-9002 AA MAN 342 M1 · VOLVO 97310 · MB 235.0 ZF TE ML-05A/07A/08/16B/16C/17B/19B /21A
ENDURANCE	140			-

CVT & DCT RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	QUALITY LEVEL of Manufacturers
ATF MAXIMA CVT	-	100% Synthetic	Volkswagen/Audi P/N G-052-180 (-A2) · Volkswagen/Audi P/N G-052-516 A2 Chrysler Mopar CVTF+4, P/N 05191184AA HONDA CVTF, P/N 08200-9006, HMMF (without start clutch) NISSAN CVT fluid NS-3, NS-2, NS-1 / NISSAN Matic W SUBARU Lineartronic, P/N K0425Y0710, e-CVTF, i-CVTF, CV-30 Suzuki CVT fluid Green 1, Green 2 · TOYOTA CVTF-FE Mercedes Benz CVT28, MB 236.20
ATF MAXIMA DCT	-	100% Synthetic	DCT TYPE VW/AUDI 7DCI600 (GS7D365G) VW/AUDI DQ250 (02E) · DQ500 (OBT) DCT (WET CLUTCH) BMW P/N 83220440214 · VW P/N G 052 182 A2
ATF MAXIMA DC TBD 8322	-	100% Synthetic	Daimler MB 239.21, MB 236.21 7G-DCT · PSA 9734 · S2 VOLVO 1161838 FORD WSS-M2C936-A · MITSUBISHI DIA QUEEN SSTF-1 GETRAG (PWA05043) GETRAG 7DCI600, 7DCT300, 6DCT450, 6DCT651 Great Wall 7DCT450 (hybrid), 7DCT300 (hybrid), 7DCT450 G2 (hybrid) Geely JL-7DCT330F (hybrid), 7DCTH390 (hybrid) BMW 83 22 0 440 214/83 22 2 147 477/83 22 2 148 578 BMW 83 22 2 148 579/83 22 2 446 673 · VW TL 52 182 (G 052 182)/DQ400E (hybrid)/DQ250, DQ500, VW DQ380

RANGO CHF RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	QUALITY LEVEL of Manufacturers
LHM	-	Mineral	UNE 26-090-88 · ISO 7308
POWER CHF	11	100% Synthetic	CHRYSLER MS-11655B · BENTLEY JNV862564F EvoBus 39.060-001 · MAN M 3289 · MB 345.0 · PSA S71 2710 BMW 81 22 9 407 758/ 82 11 1 468 041/83 29 0 429 576 FENDT X 902 011 622 · ZF TE-ML 02K (ZF000832) IVECO 18-1807 CLASSE APU · VW TL 52 146 (G 002 000) OPEL B 040 0070 · FORD M2C204-A · PORSCHE 000 043 203 33 SAAB 3032 380 · VOLVO 1161529



ATF RANGE

Name PRODUCT	NATURE	QUALITY LEVEL of Manufacturers
ATF GLOBAL MULTI	100% Synthetic	ALISON C4 · MB 236.10/236.11 · JASO 1A LV · MAN 339A VOLVO P/N 1161521 / P/N 1161540/1161640 BMW 81229400272/275 / 81229407858/859 CHRYSLER / DODGE / JEEP +2/+3/+4 / SP-III · Toyota ATF T- III / IV HYUNDAI / KIA NWS-9638 T-5 / SP-IV / SPH - IV / SP-IV-RR JAGUAR JLM 20238/20292/21044 · MAZDA F-1/ TYPE T-IV NISSAN / INFINITY MATIC - D/J/K/S/W · VW G 055 025 A2/G 052 162/G US 000162
ATF GLOBAL 295HV	100% Synthetic	ALLISON 295/389 · VOLVO 1273,41/ 97342 HONDA Z-1 · VOITH H55.6335.XX MB 236.5/236.6/236.7/236.8/236.81/236.9/236.91 JASO 1A · HYUNDAI SP-II/SP-III/JWS-3309 T-4 TOYOTA TYPE D-II/T/T-III/T-IV ZF TE-ML 11A, 11B
ATF DRAIVER DEXRON VI	100% Synthetic	GM DEXRON VI FORD MERCON LV JASO 1A LV VW G 052 162 (LIFEGUARD FLUID Z5)
ATF DRAIVER DEXRON IIIH	100% Synthetic	ALLISON C-4 Fluids, ALLISON TES, 389 · CATERPILLAR TO-2 Fluids CHRYSLER transmissions prior to CHRYSLER MS-9602 or MS-7176 FORD MERCON®; FORD M2C138-CJ, M2C 166-H Fluids GM DEXRON® III-H, III-G, III-F, III-E, III-D · MAN 339 Z1 and V1, Z2 and V2 MB 236.1, 236.5/236.6/236.7/236.9 · VOITH 55,6335 and 55,6336 VOLVO 97340/97341 ZF TE-ML 02F, 03D, 04D, 09, 11A/B, 14A/B, 16L, 17C
ATF DRAIVER DEXRON IID	Mineral	GM DEXRON II D MB 236.9 MAN 339 V-1/339 Z-1 VOITH H55.6335 ZF TE-ML 03D/04D/11A/14A/17C ALLISON C-4 FORD MERCON
ATF MAXIMA 134A	100% Synthetic	MB 236.14 SFU (suitable for use) : MB 236.1/6/7/9/10/12 SSANGYONG (MB-Automatic transmissions)
ATF MAXIMA 236.15	100% Synthetic	MB 236.15 Recommendations: MB A 001 989 78 03 / MB A 001 989 77 03 ATF 7134 FE, ATF 134 FE, ATF 134 ME
ATF MAXIMA 236.17	100% Synthetic	MB 236.17
ATF SPEED Z6	100% Synthetic	ZF 6HP19/19X/19X-Q7/21/21X/26/26A61/26A61-W12/26X/28/28A61/28AF/28X/32/32A/32X VW G055005 G 055 005 BMW 83220142516 / 83220397114 JAGUAR FLUID 8432 CHRYSLER 68157995AA LAND ROVER TYK500050 AML OIL NO. 4G4319A509-AA-S · FORD WSS-M2C949-A
ATF SPEED Z8	100% Synthetic	ZF 8 HP AUDI / VW Oil No. G 060162 A1 / A2 / A6 ATF CHRYSLER 68157995AA JAGUAR 02JDE26444 BMW 83222152426/83 22 2 289 720 FIAT 9.55550AV5 LAND ROVER LR023288 · VW 060 16



ATF RANGE

NEW

Name PRODUCT	NATURE	QUALITY LEVEL of Manufacturers
ATF FLUID D14 DRY	100% Synthetic	AIWAYS U5 · BUICK VELITE · CHERY TIGGO KUNPENG E PLUS, JETOUR X90 DONG FENG LANTUO, VOYAH (DRY MOTORS) · ENOVATE ME5 GWM ALL MODELS WITH DRY MOTOR · HOZON NETA · HYUNDAI KONA ELECTRIC KIA E-NIRO, SOUL EV, EV6 · MAXUS EUNIQ 7 · MAXUS EDELIVER 3, EDELIVER 9 MERCEDES BENZ EQE+, EQS · RIMAC NEVERA (FRONT MOTOR) PININFARINA BATTISTA (FRONT MOTOR) · SGM VELITE · WELTMEISTER EX5, EX6 VINFAST VF E34, VF E35, VF 8, VF 9
ATF FLUID D26 DRY	100% Synthetic	AUDI Q3 E-TRON, Q4 E-TRON, Q5 E-TRON · BYD ATTO 3, HAN, DOLPHIN CUPRA BORN · HONGQI E-HS · HYCAN Z03 · JAGUAR I-PACE · LIXIANG ONE NIO EC6, EL6, EL7, ES6, ET5, ET7 · PININFARINA BATTISTA (REAR AXLE) · POLESTAR 2 RIMAC NEVERA (REAR AXLE) · RIVIAN R1S, R1T · SEAT MII SKODA CITIGO-E IV, ENYAQ IV · SMART EQ FORTWO, EQ FORFOUR VOLVO XC40 RECHARGE, C40 RECHARGE · VW ID.3, ID.4, ID.5, ID.6, ID.BUZZ VW E-UP!, E-GOLF · WELTMEISTER W6 · XPENG P7, G9
ATF FLUID W400 WET	100% Synthetic	HONDA · BMW (ILINE) · MINI · MITSUBISHI · FIAT · HYUNDAI · DONG FENG · GEELY CHERY · KIA · VOLVO · NIO · LOTUS · RIMAC · RIVIAN · POLESTAR TESLA EDF-2 (1616951-04-A) · TESLA KAF 1 (1646886-04-A) · VW G 053 013



Lubricants for
AGRICULTURAL
industry



UTTO RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
UTTO FARMER	10W-30	Mineral	API GL-4(SAE 80W)	-	ALLISON C4 · CATERPILLAR TO-2 JOHN DEERE JDM J20C JI CASE MS 1207 / MS 1206 / MS 1209 / IH B6 NEW HOLLAND FNHA-2-C-201.00 CNH MAT 3525, 3526 MASSEY FERGUSON MF 1129A / MF 1135 / MF 1143 FORD M2C86-B/C, M2C134-D, FORD M2C48-C3 WHITE FARM AGCO Q-1826 VOLVO WB 101 ZF TE-ML 03E, 05F, 06K, 17E, 21F
	20W-30		API GL-4		ALLISON C-4 · JOHN DEERE JDM J20C CASE MS 1206, 1207, 1209, 1210, 1230 CNH MAT 3505, 3506, 3509, 3525, 3526 MASSEY FERGUSON CMS M 1141, 1135 AGCO POWERFLUID 821 XL · WHITE FARM AGCO Q-186 FNHA-2-C-200.00 / -201.00 FORD M2C48C3, ESN M2C86-B/C, M2C134-D NH 420-A SAE J300: 20W-30 SAE J306: 80W-85 CLAAS / SAME-TRANSMISSION/ LANDINI/ DEUTZ-FAHR FENDT
UTTO FARMER LZS	-	Mineral	API GL-4	-	ALLISON C-4 · CATERPILLAR TO-2 JOHN DEERE JDM J20D CASE MS 1210, 1209, 1207, 1206, 1205, 1204 CNH MAT 3505, 3506, 3525 MASSEY FERGUSON CMS M 1145, 1143, 1141, 1135 FORD ESN M2C41-B, M2C53-B, M2C92-A, M2C134-D FNHA-2-C-201.00 · KUBOTA UDT FLUID VOLVO VME WB 101 SAE J306: 75W ZF TE-ML 03E, 05F, 06K, 17E, 21F
UTTO MAXIMA FARMER LZS	10W-30	100% Synthetic	API GL-4	-	SAE J 306: 75W-80 · ALLISON C-4 MASSEY FERGUSON CMS 1145/ 1143/1141/1135/1129A CASE NEW HOLLAND CNH MAT 3525/3506/3505/3540 (CVT) JI CASE MS 1207 / MS 1206 / MS 1209 / MS 1210 / IH B6 JOHN DEERE JDM J20C/ JOHN DEERE JDM J20D AGCO CVT ML 200 · KOMATSU AXO 80 (KES 07.866) FORD ESN M2C134-D, FORD ESN M2C86-B/C, FORD M2C48-C3 KUBOTA UDT Fluid, Super UDT 2 VOLVO VME WB 102 ZF TE-ML 03E, 03F, 05F, 06K, 17A, 17B, 21F

STOU RANGE

Name PRODUCT	VISCOSITY Grade	NATURE	SPECIFICATIONS		QUALITY LEVEL of Manufacturers
			API/ILSAC	ACEA	
STOU AGRO	10W-30	Mineral	API CF-4, CG-4/SF API GL-4	ACEA E7	JOHN DEERE J27 MASSEY FERGUSON CMS 1145, 1144, 1139 ALLISON C4 FORD M2C159B ZF TE ML 06A, 06B, 06C, 06D, 07B CATERPILLAR TO-2 MAN 271 MIL-L-2104D MB 227.1 / MB 228.1
	15W-40				
STOU MAXIMA	10W-40	Synthetic	API CI-4 API GL-3/GL-4/API GL5 in tractors*	ACEA E7	MAN 3275 AFNOR NFE 48603 HV ALLISON C-4 CASE MS 1207, 1209, 1210, 1230, CNH MAT 3505, 3509, 3525, 3526 FNHA 2C-200.00, 201.00 FORD M2C48-C3, M2C86-B, M2C134-D, M2C159-B/C JOHN DEERE JDM J 20 C NEW HOLLAND 82009201/2/3 NH030C, NH330G, NH330H, NH410B, NH420A, NH526C MASSEY FERGUSON CMS M 1145 (1135/1139/1143/1144) ZF TE-ML 06A, 06B, 06C, 06F, 06L, 07B * no HOLMER
STOU ST	10W-40	Semi-Synthetic	API CF-4, CG-4/SF API GL-4	ACEA E7	JOHN DEERE J27 MASSEY FERGUSON CMS 1145, 1144, 1139 ALLISON C4 · FORD M2C159B ZF TE ML 06A, 06B, 06C, 06D, 07B CATERPILLAR TO-2 MAN 271 · MIL-L-2104D MB 227.1/ MB 228.1



GREASES LUBRICANTS

For **AUTOMOTIVE, MARINE, and MACHINERY** applications

GREASES LUBRICANTS	NATURE	DESCRIPTIONS
Name PRODUCT		
GRASASH AUTO 778A	Synthetic	LITHIUM COMPLEX + SYNTHETIC OIL Lithium grease for low temperatures. Complies with VW and FORD 778-A standards. Operating temperature -60 to 150°C. Applications: Mechanisms and automotive components approved under standard 778-A.
GRASASH BM MOLIX	Mineral	LITHIUM + MOLYBDENUM DISULFIDE Excellent anti-wear and antioxidant capacity. Solid EP additives. Operating temperature -20 to 120°C. Applications: Caterpillar, Hitachi, Liebherr, Volvo, Komatsu machinery DIN 51825; KPF 2K-20.
GRASASH C2	Mineral	CALCIUM Multifunctional grease with high mechanical stability, good shear resistance. Anti-corrosive properties. Operating temperature -20 to 100°C. Applications: Ball, roller, and needle bearings. DIN 51825; K 2G-20.
GRASASH GRAFOX	Mineral	ALUMINUM COMPLEX + GRAPHITE Special solid lubricant grease for the lubrication of manual gears. EP. Operating temperature -20 to 120°C. Applications: Open gears, ball mills, rotary kilns, crane cables.
GRASASH GRANCOS 900	Mineral	ALUMINUM COMPLEX + COPPER. MINERAL OIL Specially formulated for hydraulic and pneumatic hammers. Solid EP additives. Operating temperature -15 to 1100°C. Applications: Penetration and impact operations on stone and concrete. High severity.
GRASASH L2	Mineral	LITHIUM E.P. Good pumpability at low consistencies. Good shear resistance. Operating temperature -25 to 120°C. Applications: Overloaded bearings, centralized lubrication. DIN 51825 KP 2K-20.
GRASASH MARINE	Semi-Synthetic	LITHIUM-CALCIUM + SEMI-SYNTHETIC OIL Great anti-corrosive power, excellent sealing, ideal for mechanisms in humid and marine environments. Operating temperature -10 to 110°C. Applications: Bearings and surfaces exposed to direct water action.
GRASASH MAXIMA 152WR	Mineral	CALCIUM SULFONATE Calcium sulfonate grease with great anti-corrosive capacity and high performance. Operating temperature -25 to 160°C. Applications: Operations requiring a grease with high overall resistance. DIN 51825; KP 2N-10.
GRASASH SCL00	Mineral	LITHIUM E.P. For centralized lubrication and gear reducers. Soft consistency NLGI 00. Operating temperature -25 to 120°C. Applications: Overloaded bearings, centralized lubrication. DIN 51502 GP · 00G-20.



For INDUSTRIAL, PRODUCTION, and MAINTENANCE applications

GREASES LUBRICANTS	NATURE	DESCRIPTIONS
Name PRODUCT		
GRASASH COMPLEX L2A	Mineral	LITHIUM COMPLEX + MINERAL OIL Multifunctional lithium grease for high temperatures. Operating temperature -30 to 150°C. Applications: General lubrication in medium-high temperature environments.
GRASASH COMPLEX 170A	Mineral	LITHIUM COMPLEX + MINERAL OIL Lithium grease with special adhesion for high temperatures. Operating temperature -15 to 170°C. Applications: Mechanisms with high loads and vibrations. Up to temperatures of 200°C.
GRASASH COMPLEX S150	Synthetic	LITHIUM COMPLEX + SYNTHETIC OIL Special synthetic grease for high speeds. Excellent adhesion and shear stability. Operating temperature -55 to 150°C. Applications: Machine tool heads. High-speed bearings and spindles.
GRASASH COMPLEX S180	Synthetic	LITHIUM COMPLEX + SYNTHETIC OIL High performance and very wide temperature range. Water and steam resistance. Operating temperature -40 to 180°C. Applications: Bearings under severe load conditions. Minimal need for relubrication.
GRASASH MAXIMA MOLIX	Mineral	CALCIUM SULFONATE + MOLYBDENUM DISULFIDE High performance, great anti-corrosive capacity, and high workload. Operating temperature -25 to 160°C. Applications: Bearings, cables, and rolling mill chains in aggressive environments.
GRASASH METAL BRAID	Mineral	INORGANIC + MINERAL OIL + S2 MO Highly corrosion-resistant fluid grease, penetrating with solid lubricants. Operating temperature -10 to 150°C. Applications: Lubrication of metal cables. Dry lubrication up to 450°C.
GRASASH PASTE 1100	Mineral	INORGANIC + MINERAL OIL Copper anti-seize paste. High anti-corrosive capacity. Total permanence. Operating temperature -15 to 1100°C. Applications: Protection of all types of bolts and threaded connections.
GRASASH POLY T180	Synthetic	POLYUREA + SYNTHETIC OIL Multipurpose high-temperature grease. Up to 220°C. High viscosity index. Operating temperature -50 to 180°C. Applications: Machine tool heads. High-speed bearings and spindles.
GRASASH POLY T200	Synthetic	POLYUREA + SYNTHETIC OIL Polyurea grease with synthetic oil, long-lasting, for high temperatures and heavy loads. Operating temperature -20 to 200°C. Applications: Oven bearings and/or high levels of contamination.



For HIGH-PERFORMANCE applications

GREASES LUBRICANTS	NATURE	DESCRIPTIONS
Name PRODUCT		
GRASASH COMPLEX ELECTRON	Synthetic	LITHIUM COMPLEX + SYNTHETIC OIL Lubrication and anti-corrosive protection. High conductivity. Operating temperature -70 to 130°C. Applications: Lubrication and protection of electrical contacts. Electronic circuits.
GRASASH PASTE 1180	Mineral	INORGANIC + MINERAL OIL + ALUMINUM POWDER Copper-free anti-seize paste. Anti-corrosive. High conductivity. Operating temperature -15 to 1180°C. Applications: Protection against seizing, corrosion, and galling. Assembly and disassembly of treated parts.
GRASASH SUPREME T100	Synthetic	INORGANIC + SYNTHETIC OIL + S2 MO High temperature resistance. Excellent anti-corrosive and anti-wear properties. Operating temperature -35 to 220°C. Applications: Steel bearings, wagon wheels, electric motors.
GRASASH SUPREME T200	Semi-Synthetic	INORGANIC + SEMI-SYNTHETIC OIL + SOLIDS Stability under very high loads. Water repellent. Extreme adhesion. Operating temperature -10 to 150°C. Applications: Lubrication of all types of open gears and slewing rings.
GRASASH SUPREME T300	Mineral	ORGANIC POLYESTER + FLUORINATED Excellent resistance to oxygen, chemical agents, and high temperatures. Unalterable. Operating temperature -25 to 260°C. Applications: Bearings in critical conditions. Extremely high temperatures and aggressive environments.
GRASASH SUPREME T400	Mineral	ORGANIC POLYESTER + FLUORINATED Unalterable against synthetic materials and elastomers. Resistant to oxygen, chemicals, and high temperatures. Operating temperature -25 to 280°C. Applications: In general, where a long-lasting lubricant is required under conditions of extremely high temperatures and aggressive environments.
GRASASH SUPREME T500	Mineral	PTFE + PTFE OIL White and homogeneous grease, based on fluorinated polyester. Exceptional chemical and high-temperature stability. Operating temperature -25 to 260°C. Applications: Bearings in critical conditions: corrugated cardboard, transport chains in drying facilities, kiln wagons.



For low environmental impact and BIODEGRADABLE

GREASES LUBRICANTS	NATURE	DESCRIPTIONS
Name PRODUCT		
GRASASH BIO E200	Mineral	LITHIUM HYDROXYSTEARATE + NATURAL ESTER CEC L33-A-93 biodegradability test. Minimum 80%. Operating temperature -25 to 120°C. Applications: Bearing lubrication. High sealing capacity.
GRASASH BIO E300	Mineral	LITHIUM HYDROXYSTEARATE + NATURAL ESTER CEC L33-A-93 biodegradability test. Minimum 80%. Operating temperature -25 to 120°C. Applications: Lubrication of multipurpose mechanisms. High pumpability.
GRASASH BIO E400	Mineral	LITHIUM HYDROXYSTEARATE + NATURAL ESTER + GRAPHITE CEC L33-A-93 biodegradability test. Minimum 80%. Operating temperature -30 to 80°C. Applications: Bearings and mechanisms with loads. Tracks, guides, and telescopic systems. NLGI 2.
GRASASH BIO E600	Mineral	LITHIUM HYDROXIESTEARE + NATURAL ESTER + GRAPHITE Biodegradability test CEC L33-A-93. Min 80%. Work Temperature -30 to 80°C. Applications: Automatic lubrication lines and systems. Excellent pumpability. Railroad tracks. Forest industry.



AUXILIARY

products



ANTIFREEZE & WINDSHIELD CLEANERS

NEW

ANTIFREEZE & WINDSHIELD CLEANERS	COLOR	QUALITY LEVEL of Manufacturers	DESCRIPTIONS
Name PRODUCT			
LUBCOLD ORGANIC 10%	Fluorescent green ●	UNE 26.361.88 ASTM D-3306 BS 6580	Ready-to-use coolant antifreeze formulated with ethylene glycol and additives to protect vehicle and machinery circuits, especially high-pressure aluminum engines. Free of NAP, it provides high anti-corrosion protection, good thermal transfer, is biodegradable, and compatible with system components.
LUBCOLD ORGANIC 30%	Green ●	UNE 26.361.88 · ASTM D-3306/D-4985 BS 6580 · SAE J 1034, J 814 Y J 1941 MB-APPROVAL 325.3 · FORD WSS-M97B44-D GENERAL MOTORS GM 6277M VOLKSWAGEN VW 774 F · DEUTZ DQC CB-14 MAN 324 TIPO SNF · DAF 74002 CATERPILLAR A4.05.09.01 RENAULT TRUCKS 41-01-001/--S TYPE D	Ready-to-use coolant antifreeze formulated with ethylene glycol and additives to protect vehicle and machinery circuits, especially high-pressure aluminum engines. Free from NAP, it provides excellent anti-corrosion protection, good thermal transfer, is biodegradable, and compatible with system components.
LUBCOLD G12 EVO 50%	Pink ●	VOLKSWAGEN GROUP TL 774-L/G-12 EVO (AUDI, VW, SEAT, SKODA) UNE 26-361-88 · ASTM D-3306-00 · ASTM D-4985-94 FORD WSS-M97B44D · MB 325.3 · FIAT 9.55523 · SAE J 1034/91 GENERAL MOTORS 6277M PSA PEUGEOT-CITROËN B71-5110 RENAULT 41-01-001/Q-TYPE D NISSAN BS 6580 · DAF 74002 HONDA HES D2009-75 · DETROIT DIESEL · DEUTZ 0199-99-1115 LEYLAND TRUCKS DW03245403 ISUZU · MAN 324 TYPE SNF MB 325.3 · MB 326.3 · MTU MTL 5048 · VOLVO VCS RENAULT TRUCKS 41-01-001/S TYPE D SCANIA TB 1451 · CATERPILLAR-MAK A4.05.09.01 KOBELCO · KOMATSU 07.892 LIEBHERR MD1-36-130	Ready-to-use coolant antifreeze formulated with ethylene glycol and additives to protect vehicle and machinery circuits, especially high-pressure aluminum engines. Free from NAP, it provides high anti-corrosion protection, good thermal transfer, is biodegradable, and compatible with system components.
LUBCOLD G12/G12+ 50%	Pink ●	LIGHT VEHICLES: UNE 26-361-88 · ASTM D-3306 ASTM D-4985-94 FORD WSS-M97B44D FIAT 9.55523 · SAE J 1034/91 GENERAL MOTORS 6277M MB 325.3 PSA PEUGEOT-CITROËN B71-5110 RENAULT 41-01-001/Q type d NISSAN · BS 6580 HONDA HES D2009-75 BS 6580	Ready-to-use coolant antifreeze formulated with ethylene glycol and additives to protect vehicle and machinery circuits, especially high-pressure aluminum engines. Free from NAP, it provides high anti-corrosion protection, good thermal transfer, is biodegradable, and compatible with system components.
		HEAVY VEHICLES: DAF 74002 · DETROIT DIESEL · ISUZU DEUTZ 0199-99-115 · KOBELCO LIEBHERR MD1-36-130 DEUTZ/MWM 0199-99-2091 · VOLVO VCS LEYLAND TRUCKS DW03245403 MAN 324 TYPE SNF · KOMATSU 07.892 MB 325.3 – MB 326.3 MTU MTL 5048 · SCANIA TB 1451 RENAULT TRUCKS 41-01-001/S TYPE D CATERPILLAR-MAK A4.05.09.01	
LUBCOLD G12++ 50%	Pink ●	UNE 26-361-88 · ASTM D-3306 ASTM D-4985-94 · FORD WSS-M97B44D MB 325.3 · FIAT 9.55523 · SAE J 1034/91 SAE J 1814 · GENERAL MOTORS 6277M PSA PEUGEOT-CITROËN B71-5110 RENAULT 41-01-001/Q type d NISSAN · BS 6580 HONDA HES D2009-75 BS 6580	Ready-to-use coolant antifreeze formulated with ethylene glycol and additives to protect vehicle and machinery circuits, especially high-pressure aluminum engines. Free from NAP, it provides high anti-corrosion protection, good thermal transfer, is biodegradable, and compatible with system components.
LUBCOLD PURO 100%	Yellow ●	AS 2108-2004, ASTM D 3306, ASTM D 4985, ASTM D 6210 SAE J1034, ÖNORM V 5123, CUNA NC 956-16, JIS K 2234:2006 MAN 324 TYPE SI-OAT SANS 1251:2005, SH 0521-1999 AND BS 6580:2010 VW / AUDI / SEAT / SKODA TL 774-G (G12++) LAMBORGHINI / BENTLEY / BUGATTI MB 325.0 MB 325.5 MB 326.5 MB 326.0 MB 326.6 CUMMINS CES 14603 DEUTZ DQC CC-14 LIEBHERR MINIMUM LH-01 COL3A SCANIA TB 145 Diluted at 50%. Exceeds G-12/G-12+ levels.	Meets major international standards such as AS 2108-2004, ASTM D3306, D4985, D6210, SAE J1034, ÖNORM V 5123, CUNA NC 956-16, JIS K 2234:2006, among others. Approved by manufacturers such as MAN (324 TYPE SI-OAT), VW/AUDI/SEAT/SKODA (TL 774-G G12++), Mercedes-Benz (MB 325.0, 325.5, 326.0, 326.5, 326.6), Cummins, DEUTZ, LIEBHERR, and Scania. Suitable for Lamborghini, Bentley, and Bugatti vehicles. Product diluted at 50% with performance exceeding G12/G12+ standards.




NEW

ANTIFREEZE & WINDSHIELD CLEANERS	COLOR	QUALITY LEVEL of Manufacturers	DESCRIPTIONS
Name PRODUCT			
LUBCOLD G12/G12+ TRUCK 50%	Pink 	LIGHT VEHICLES: UNE 26-361-88 ASTM D-3306 / ASTM D-4985-94 FORD WSS-M97B44D MB 325.3 · FIAT 9.55523 SAE J 1034/91 GENERAL MOTORS 6277M PSA PEUGEOT-CITROËN B71-5110 RENAULT 41-01-001/Q type d NISSAN · BS 6580 HONDA HES D2009-75 BS 6580 HEAVY VEHICLES: DAF 74002 · DETROIT DIESEL DEUTZ 0199-99-115 DEUTZ/MWM 0199-99-2091 ISUZU · LEYLAND TRUCKS DW03245403 MAN 324 TYPE SNF · MB 325.3 – MB 326.3 MTU MTL 5048 RENAULT TRUCKS 41-01-001/S TYPE D SCANIA TB 1451 · VOLVO VCS CATERPILLAR-MAK A4.05.09.01 KOBELCO · KOMATSU 07.892 LIEBHERR MD1-36-130	Ready-to-use coolant antifreeze formulated with ethylene glycol and additives to protect vehicle and machinery circuits, especially high-pressure aluminum engines. Free from NAP, it provides high anti-corrosion protection, good thermal transfer, is biodegradable, and compatible with system components.
LUBCOLD G12++ TRUCK SI-OAT 50%	Pink 	HEAVY AGRICULTURAL VEHICLES: DAF 74002 · DETROIT DIESEL DEUTZ 0199-99-115 DEUTZ/MWM 0199-99-2091 · ISUZU LEYLAND TRUCKS DW03245403 MAN 324 TYPE SI-OAT MTU MTL 5048 MB 325.5 – MB 325.6 – MB 326.5 RENAULT TRUCKS 41-01-001/S TYPE D SCANIA TB 1451 · VOLVO VCS · VW TL 774-G CATERPILLAR-MAK A4.05.09.01 KOBELCO · KOMATSU 07.892 LIEBHERR LH-01-COL3A CUMMINS CES 14603	Ready-to-use coolant antifreeze, compatible with MAN 324 Type SI-OAT (EURO 6), ideal for heavy vehicles, machinery, and stationary engines. Provides corrosion protection, is NAP free, biodegradable, and suitable for high-pressure aluminum engines. Not suitable for domestic heating.
LUBCOLD CONCENTRADO SI-OAT	Yellow 	-	-
LUBCOLD LP -10°C	Blue 	-	Ready-to-use windshield washer fluid with antifreeze protection down to -10 °C. Dissolves dirt on the glass, prevents blockages and freezing of the system, does not damage rubber or paint, and leaves no residue on the windshield.
LUBCOLD LP VERANO ANTIMOSQUITOS	Blue 	-	Ready-to-use anti-insect windshield washer, specially formulated to remove dirt and insects without clogging the nozzles, without damaging rubber or paint, and leaving no residue on the glass.



BRAKE PRODUCTS

NEW

Name PRODUCT	QUALITY LEVEL of Manufacturers	DESCRIPTIONS
XTR 5000 BRAKE CLEANER	-	Quick and safe cleaning for brakes and clutches.
BRAKE-CLEAN MAXIMA	-	-
DOT-4	PN-C-40005 FMVSS No. 116 ISO 4925 SAE J 1704	High-quality brake fluid that ensures quick system response even at low temperatures. It provides excellent protection against corrosion, prevents deposit formation, and extends the service life of brake and clutch systems in all types of vehicles.

PENETRATING OIL RELEASE AGENT – ANTIOXIDANT PROTECTOR

Name PRODUCT	DESCRIPTIONS
AFLOSH - DOBEL	PROTECTOR Multi-Purpose Penetrating Oil – Antioxidant. Color red

CLEANING ABSORBENTS

Name PRODUCT	DESCRIPTIONS
SEPIOLITA 15/30	EXTRA

FOR CLEANING THERMAL CIRCUITS

Name PRODUCT	DESCRIPTIONS
LIMEMUL CONCENTRADO	Recommended cleaning dosage: 2% to 5%. Recommended maintenance dosage: 0.5% to 1%.



SANITIZERS / DEGREASERS

Name PRODUCT	DESCRIPTIONS
WS 3527 S	Combines cleaning and hygiene properties with excellent synergy. (Skin, glasses, helmets, railings, doorknobs, car steering wheels, office furniture, home, toys, etc.). Spray/Aerosol. Specific disinfectant cleaner.
ELITE PASTA XP	Medium severity for heavy dirt. Approximately 200 APPLICATIONS. Traditional hand cleaner paste with natural abrasive, containing glycerin. RECOMMENDED FOR: GREASY DIRT – Grease, Oil, Lubricants, Hydrocarbons, Bitumen.
ELITE CREAM	High severity against dirt. Approximately 1175 APPLICATIONS. Hand cleaner cream with natural microbeads. RECOMMENDED FOR: GREASY DIRT – Grease, Oil, Lubricants, Hydrocarbons, Bitumen. DRY DIRT – Fresh Paint, Enamel, Silicone, Graphite, Glue, Mold, Resin...
SOPORTE PARED ELITE 5KGS	RECOMMENDED FOR: ELITE CREAM / ELITE TOPGIEN

ADDITIVES FOR AUTOMOTIVE

Name PRODUCT	DESCRIPTIONS
ANTIFREEZING FOR DIESEL	Antifreeze – Anti-Smoke Additive for Diesel. This additive is specially designed for diesel, with the ability to enhance fuel service performance.
FOR DIESEL	Diesel Anti-Smoke Additive. The additive is formulated to prevent freezing caused by the presence of waxes in the oil and to prevent black smoke from combustion. This additive is specially designed for diesel, with the ability to enhance fuel service performance.
ADITIVE DIESEL FUNGI-8417B	Special Additive for Diesel FUNGICIDE / BACTERICIDE Excellent high-quality additive for diesel, with powerful fungicidal and bactericidal properties.



POWERBOOST

additives



POWERBOOST ADDITIVES

NEW

POWERBOOST ADDITIVES	DESCRIPTIONS
Name PRODUCT	
PCX 200 OCTANE BOOSTER	High-performance package tested in motorsports. Increases gasoline octane rating, optimizes combustion, improves fuel efficiency, torque, and acceleration. Cleans the fuel system and injectors, preventing costly repairs, and protects exhaust valves in classic cars.
PCX 600 PETROL INJECTOR CLEANER	Removes deposits from injectors, valves, spark plugs, and combustion chamber, preventing their formation. Improves starting, smooths engine operation, and protects against corrosion. Optimizes performance, compression, and emissions, reducing fuel consumption and pollutants.
PCX 500 DIESEL SYSTEM CLEANER	Formulated for high-pressure diesel engines, it enhances lubrication and cleaning, protects against wear, and optimizes precision injectors. Improves cold combustion and reduces exhaust gas odors.
PCX 800 CETAN BOOSTER	Cetane booster to improve fuel combustibility. Increases the cetane number of diesel fuel by up to 5 points. Recommended for lower-quality fuels and during the winter season.
PCX DPF PREMIUM	Optimizes combustion, reduces soot and emissions, and extends the lifespan of diesel particulate filters. Ideal for vehicles on short and urban trips, it prevents blockages and costly repairs with regular use.
TMX 1500 CERAMIC ADDITIVE	Suspension of solid micro-ceramic lubricant based on hexagonal boron nitride (BN). Reduces friction and wear, preventing metal-to-metal contact. With particles <0.5 µm, it ensures optimal flow and compatibility with all commercial engine and gear oils.
TMX EFA500 ENGINE FLUSH	Highly effective detergent and dispersant additives remove soluble and insoluble deposits, suspending them for removal during the next oil change. Ensures a clean engine for maximum performance of fresh oil.
TMX SS300 OIL PERFORMANCE IMPROVER	High-performance additive that stabilizes oil viscosity, protects against mechanical loss, and prevents thinning under extreme conditions and frequent cold starts.
TMX USL700 RADIATOR SEAL	Seals fine cracks and small leaks in water-cooled engine cooling systems. Useful as a preventive measure after repairs. Contains a stabilized dispersion of solids in a carrier fluid.





POWERBOOST ADDITIVES	DESCRIPTIONS
Name PRODUCT	
TMX D BLUE	Additive designed to keep the SCR system clean: prevents the formation of AdBlue crystals, dissolves existing deposits, and protects the catalyst and injectors. Its use reduces pollutant emissions, extends the service life of the system, and helps avoid costly repairs.
XTR CHAIN OIL	Lubricant spray for motorcycle chains that reduces friction, protects, and extends their service life. It is applied to a clean chain, shaking well before use and wiping off any excess with a cloth. Repels moisture, offers high wear resistance, and retains its properties. Must be stored in closed containers, in a cool, dry, and ventilated place, between +5 and +25 °C, with a minimum shelf life of 4 years from the date of manufacture.



ACEITES LUBRICANTES SASH
www.lubricantes-sash.com | sash@lubricantes-sash.com
+34 961 464 843